

Software RAID (mdadm) - Running RAID 0 alongside RAID 1

Draft - Incomplete, but kept mostly for my own sake so I can find my way back to it at a later date.

- Specific scenario: Hetzner installimage with RAID1 or RAID10
- RAID10 with less storage for the OS and "important" stuff.
 - Make sure to comment out the `all` option, that allocates the rest of the disks to say `/home` or similar.
- RAID0 with the remaining storage across all 4 of the disks (Linux ISOs) that's easily replacable.

1. Create empty partitions using `fdisk`. Ended up with: `/dev/sda5`, `/dev/sdb5` etc.

- `fdisk /dev/sda`
 - `n` (new partition)
 - Note the partition number. For me the last partition number ended up being `5` for all disks, which I used in the `mdadm` command later.
 - Select start block, end block etc. (or just leave default to use remaining space)
 - `w` to write partition table

2. Create a new RAID0 array using new partitions, with `mdadm`:

- `mdadm --create --verbose /dev/md3 --level=0 --raid-devices=4 /dev/sda5 /dev/sdb5 /dev/sdc5 /dev/sdd5`

- Note: Might wanna check `lsblk` to verify that `/dev/md3` isn't already taken. When I ran `installimage` I ended up with:

- `md0` = swap
- `md1` = boot
- `md2` = root partition (`/`)

3. Run `mdadm --detail --scan` and find the line that matches `/dev/md3`. Copy that line and put it at the end of `/etc/mdadm/mdadm.conf`

- A lot of tutorials suggest piping that to `tee -a /etc/mdadm/mdadm.conf` so it appends **all** the lines to the end of `/etc/mdadm/mdadm.conf`. In this case since there's already an existing RAID array, there will be duplicate lines and potential for conflicts.

4. Double check that `/etc/mdadm/mdadm.conf` looks correct, then run `update-initramfs -u` so that the RAID array is available during the boot process.

- TODO: Creating filesystem, mounting, append to fstab.

Revision #4

Created 2022-07-16 21:50:51 UTC by Alex Thomassen

Updated 2023-03-27 14:03:11 UTC by Alex Thomassen